



KILREMSSKIVOR FÖR TAPER LOCK BUSSNING

V-BELTS PULLEYS FOR TAPER BUSH


SPC - 3



1



3



4

Material: Gjutjärn EN-GJL-200

Benämning	Artikelnr.	Antal spår	dp	de	Typ	För bussning	Axelhål max	Dm	Di	E	F	L	R	S	Kg.
SPC 200x3	3SPC200	3	200	209,6	3	2517	65		144	85	45	20	20		10,00
SPC 212x3	3SPC212	3	212	221,6	3	3020	75		156	85	51	17	17		10,60
SPC 224x3	3SPC224	3	224	233,6	3	3020	75		168	85	51	17	17		12,40
SPC 236x3	3SPC236	3	236	245,6	3	3020	75		180	85	51	17	17		14,10
SPC 250x3	3SPC250	3	250	259,6	3	3020	75		194	85	51	17	17		16,00
SPC 265x3	3SPC265	3	265	274,6	1	3535	90	175		85	89	4			23,00
SPC 280x3	3SPC280	3	280	289,6	1	3535	90	175		85	89	4			26,50
SPC 300x3	3SPC300	3	300	309,6	4	3535	90	175	244	85	89	2	2		20,50
SPC 315x3	3SPC315	3	315	324,6	4	3535	90	175	259	85	89	2	2		21,50
SPC 335x3	3SPC335	3	335	344,6	4	3535	90	175	279	85	89	2	2		23,50
SPC 355x3	3SPC355	3	355	364,6	4	3535	90	175	299	85	89	2	2		24,50
SPC 375x3	3SPC375	3	375	384,6	4	3535	90	175	319	85	89	2	2		25,50
SPC 400x3	3SPB400	3	400	409,6	4	3535	90	175	344	85	89	2	2		27
SPC 425x3	3SPC425	3	425	434,6	4	3535	90	175	369	85	89	2	2		29
SPC 450x3	3SPC450	3	450	459,6	4	3535	90	175	394	85	89	2	2		32
SPC 475x3	3SPC475	3	475	484,6	4	3535	90	175	419	85	89	2	2		34
SPC 500x3	3SPC500	3	500	509,6	4	3535	90	175	444	85	89	2	2		36
SPC 530x3	3SPC530	3	530	539,6	4	3535	90	175	474	85	89	2	2		38
SPC 560x3	3SPC560	3	560	569,6	4	3535	90	175	504	85	89	2	2		40
SPC 630x3	3SPC630	3	630	639,6	4	4040	100	210	574	85	102	8,5	8,5		52
SPC 800x3	3SPC800	3	800	809,6	4	4545	110	242	737	85	114	14,5	14,5		80
SPC 1000x3	3SPC1000	3	1000	1009,6	4	5050	125	267	937	85	127	21	21		113
SPC 1250x3	3SPC1250	3	1250	1259,6	4	5050	125	267	1187	85	127	21	21		138




info@transflex.nu


KILREMSSKIVOR FÖR TAPER LOCK BUSSNING

V-BELTS PULLEYS FOR TAPER BUSH


SPC - 4




3



4



5



6

Material: Gjutjärn EN-GJL-200

Benämning	Artikelnr.	Antal spår	dp	de	Typ	För bussning	Axelhål max	Dm	Di	E	F	L	R	S	Kg.
SPC 200x4	4SPC200	4	200	209,6	3	3020	75		144	111	51	30	30	11	
SPC 212x4	4SPC212	4	212	221,6	3	3020	75		156	111	51	30	30	12,50	
SPC 224x4	4SPC224	4	224	233,6	3	3535	90		168	111	89	11	11	16	
SPC 236x4	4SPC236	4	236	245,6	3	3535	90		180	111	89	11	11	18,50	
SPC 250x4	4SPC250	4	250	259,6	3	3535	90		194	111	89	11	11	22	
SPC 265x4	4SPC265	4	265	274,6	3	3535	90		209	111	89	11	11	26	
SPC 280x4	4SPC280	4	280	289,6	6	3535	90	175	224	18	89	11	11	25,40	
SPC 300x4	4SPC300	4	300	309,6	6	3535	90	175	244	20	89	11	11	30	
SPC 315x4	4SPC315	4	315	324,6	5	3535	90	175	259		111	89	11	11	24
SPC 335x4	4SPC335	4	335	344,6	5	3535	90	175	279		111	89	11	11	27
SPC 355x4	4SPC355	4	355	364,6	5	3535	90	175	299		111	89	11	11	28,30
SPC 375x4	4SPC375	4	375	384,6	5	3535	90	175	319		111	89	11	11	30
SPC 400x4	4SPC400	4	400	409,6	5	3535	90	175	344		111	89	11	11	34
SPC 425x4	4SPC425	4	425	434,6	5	3535	90	175	369		111	89	11	11	35
SPC 450x4	4SPC450	4	450	459,6	5	3535	90	175	394		111	89	11	11	37
SPC 475x4	4SPC475	4	475	484,6	5	3535	90	175	419		111	89	11	11	39
SPC 500x4	4SPC500	4	500	509,6	5	3535	90	175	444		111	89	11	11	43
SPC 530x4	4SPC530	4	530	539,6	5	4040	100	210	474		111	102	4,5	4,5	50
SPC 560x4	4SPC560	4	560	569,6	5	4040	100	210	504		111	102	4,5	4,5	54
SPC 630x4	4SPC630	4	630	639,6	4	4545	110	242	574		111	114	1,5	1,5	66
SPC 710x4	4SPC710	4	710	719,6	4	5050	125	267	654		111	127	8	8	82
SPC 800x4	4SPC800	4	800	809,6	4	5050	125	267	737		111	127	8	8	100
SPC 1000x4	4SPC1000	4	1000	1009,6	4	5050	125	267	937		111	127	8	8	126
SPC 1250x4	4SPC1250	4	1250	1259,6	4	5050	125	267	1187		111	127	8	8	175




info@transflex.nu


KILREMSSKIVOR FÖR TAPER LOCK BUSSNING

V-BELTS PULLEYS FOR TAPER BUSH


SPC - 5




3



4



5



6

Material: Gjutjärn EN-GJL-200

Material: Gjutjärn EN-GJS-250																
Benämning		Artikelnr.	Antal spår	dp	de	Typ	För bussning	Axelhål max	Dm	Di	E	F	L	R	S	Kg.
SPC	200x5	5SPC200	5	200	209,6	3	3535	90		144		136	89	23,5	23,5	13,00
SPC	212x5	5SPC212	5	212	221,6	3	3535	90		156		136	89	23,5	23,5	15,60
SPC	224x5	5SPC224	5	224	233,6	3	3535	90		168		136	89	23,5	23,5	18,40
SPC	236x5	5SPC236	5	236	245,6	3	3535	90		180		136	89	23,5	23,5	21,20
SPC	250x5	5SPC250	5	250	259,6	3	3535	90		194		136	89	23,5	23,5	24,70
SPC	265x5	5SPC265	5	265	274,6	3	3535	90		209		136	89	23,5	23,5	28,60
SPC	280x5	5SCP280	5	280	289,6	3	3535	90		224		136	89	23,5	23,5	33,00
SPC	300x5	5SPC300	5	300	309,6	6	3535	90	175	244	20	136	89	23,5	23,5	30,50
SPC	315x5	5SPC315	5	315	324,6	5	3535	90	175	259		136	89	23,5	23,5	28,00
SPC	335x5	5SPC335	5	335	344,6	5	3535	90	175	279		136	89	23,5	23,5	31,00
SPC	355x5	5SPC355	5	355	364,6	5	3535	90	175	299		136	89	23,5	23,5	33,50
SPC	375x5	5SPC375	5	375	384,6	5	3535	90	175	319		136	89	23,5	23,5	35,00
SPC	400x5	5SPC400	5	400	409,6	5	3535	90	175	344		136	89	23,5	23,5	37,00
SPC	425x5	5SPC425	5	425	434,6	5	3535	90	175	369		136	89	23,5	23,5	40,00
SPC	450x5	5SPC450	5	450	459,6	5	4040	100	210	394		136	102	17	17	46,00
SPC	475x5	5SPC475	5	475	484,6	5	4040	100	210	419		136	102	17	17	50,30
SPC	500x5	5SPC500	5	500	509,6	5	4040	100	210	444		136	102	17	17	53,00
SPC	530x5	5SPC530	5	530	539,6	5	4545	110	240	474		136	114	11	11	65,00
SPC	560x5	5SPC560	5	560	569,6	5	4545	110	242	504		136	114	11	11	68,00
SPC	630x5	5SPC630	5	630	639,6	5	5050	125	267	574		136	127	4,5	4,5	81,00
SPC	710x5	5SPC710	5	710	719,6	5	5050	125	267	654		136	127	4,5	4,5	96,50
SPC	800x5	5SPC800	5	800	809,6	5	5050	125	267	737		136	127	4,5	4,5	94,00
SPC	1000x5	5SPC1000	5	1000	1009,6	5	5050	125	267	937		136	127	4,5	4,5	139
SPC	1250x5	5SPC1250	5	1250	1259,6	5	5050	125	267	1187		136	127	4,5	4,5	191




info@transflex.nu


KILREMSSKIVOR FÖR TAPER LOCK BUSSNING

V-BELTS PULLEYS FOR TAPER BUSH


SPC - 6



3



5



6

Material: Gjutjärn EN-GJL-200

Benämning	Artikelnr.	Antal spår	dp	de	Typ	För bussning	Axelhål max	Dm	Di	E	F	L	R	S	Kg.
SPC 200x6	6SPC200	6	200	209,6	3	3535	90		144	162	89	36,5	36,5	15	
SPC 212x6	6SPC212	6	212	221,6	3	3535	90		156	162	89	36,5	36,5	17,80	
SPC 224x6	6SPC224	6	224	233,6	3	3535	90		168	162	89	36,5	36,5	20,50	
SPC 236x6	6SPC236	6	236	245,6	3	3535	90		180	162	89	36,5	36,5	23,50	
SPC 250x6	6SPC250	6	250	259,6	3	3535	90		194	162	89	36,5	36,5	27,20	
SPC 265x6	6SPC265	6	265	274,6	3	3535	90		209	162	89	36,5	36,5	31	
SPC 280x6	6SCP280	6	280	289,6	6	3535	90	175	224	20	162	89	36,5	36,5	28
SPC 300x6	6SPC300	6	300	309,6	6	3535	90	175	244	20	162	89	36,5	36,5	31,50
SPC 315x6	6SPC315	6	315	324,6	5	3535	90	175	259		162	89	36,5	36,5	32
SPC 335x6	6SPC335	6	335	344,6	5	3535	90	175	279		162	89	36,5	36,5	35
SPC 355x6	6SPC355	6	355	364,6	5	3535	90	175	299		162	89	36,5	36,5	37
SPC 375x6	6SPC375	6	375	384,6	5	4040	100	210	319		162	102	30	30	46
SPC 400x6	6SPC400	6	400	409,6	5	4040	100	210	344		162	102	30	30	48
SPC 425x6	6SPC425	6	425	434,6	5	4040	100	210	369		162	102	30	30	51
SPC 450x6	6SPC450	6	450	459,6	5	4545	110	242	394		162	114	24	24	60
SPC 475x6	6SPC475	6	475	484,6	5	4545	110	242	419		162	114	24	24	63
SPC 500x6	6SPC500	6	500	509,6	5	4545	110	242	444		162	114	24	24	68
SPC 530x6	6SPC530	6	530	539,6	5	5050	125	265	474		162	127	17,5	17,5	76
SPC 560x6	6SPC560	6	560	569,6	5	5050	125	267	504		162	127	17,5	17,5	81
SPC 630x6	6SPC630	6	630	639,6	5	5050	125	267	574		162	127	17,5	17,5	90
SPC 710x6	6SPC710	6	710	719,6	5	5050	125	267	654		162	127	17,5	17,5	103
SPC 800x6	6SPC800	6	800	809,6	5	5050	125	267	737		162	127	17,5	17,5	123
SPC 1000x6	6SPC1000	6	1000	1009,6	5	5050	125	267	937		162	127	17,5	17,5	160
SPC 1250x6	6SPC1250	6	1250	1259,6	5	5050	125	267	1187		162	127	17,5	17,5	204




info@transflex.nu


KILREMSSKIVOR FÖR TAPER LOCK BUSSNING

V-BELTS PULLEYS FOR TAPER BUSH


SPC - 8



3



5



6

Material: Gjutjärn EN-GJL-200

Benämning	Artikelnr.	Antal spår	dp	de	Typ	För bussning	Axelhål max	Dm	Di	E	F	L	R	S	Kg.
SPC 200x8	8SPC200	8	200	209,6	3	3535	90		144	213	89	62,0	62,0	19	
SPC 212x8	8SPC212	8	212	221,6	3	3535	90		156	213	89	62,0	62,0	21,60	
SPC 224x8	8SPC224	8	224	233,6	3	3535	90		168	213	89	62,0	62,0	25,00	
SPC 236x8	8SPC236	8	236	245,6	3	3535	90		180	213	89	62,0	62,0	27,00	
SPC 250x8	8SPC250	8	250	259,6	3	3535	90		194	213	89	62,0	62,0	31,50	
SPC 265x8	8SPC265	8	265	274,6	3	3535	90		209	213	89	62,0	62,0	37	
SPC 280x8	8SPC280	8	280	289,6	3	3535	90		224	213	89	62,0	62,0	40	
SPC 300x8	8SPC300	8	300	309,6	3	4040	100		244	213	102	55,5	55,5	48,50	
SPC 315x8	8SPC315	8	315	324,6	3	4040	100		259	213	102	55,5	55,5	53	
SPC 335x8	8SPC335	8	335	344,6	6	4040	100	210	279	50	213	102	55,5	55,5	53
SPC 355x8	8SPC355	8	355	364,6	5	4040	100	210	299		213	102	55,5	55,5	50
SPC 375x8	8SPC375	8	375	384,6	5	4545	110	242	319		213	114	50	50	61
SPC 400x8	8SPC400	8	400	409,6	5	4545	110	242	344		213	114	50	50	65
SPC 425x8	8SPC425	8	425	434,6	5	4545	110	242	369		213	114	50	50	71
SPC 450x8	8SPC450	8	450	459,6	5	5050	125	267	394		213	127	43	43	79
SPC 475x8	8SPC475	8	475	484,6	5	5050	125	267	419		213	127	43	43	84
SPC 500x8	8SPC500	8	500	509,6	5	5050	125	267	444		213	127	43	43	88
SPC 530x8	8SPC530	8	530	539,6	5	5050	125	267	474		213	127	43,0	43,0	91
SPC 560x8	8SPC560	8	560	569,6	5	5050	125	267	504		213	127	43,0	43,0	97
SPC 630x8	8SPC630	8	630	639,6	5	5050	125	267	574		213	127	43,0	43,0	110
SPC 710x8	8SPC710	8	710	719,6	5	5050	125	267	654		213	127	43,0	43,0	121
SPC 800x8	8SPC800	8	800	809,6	5	5050	125	267	737		213	127	43,0	43,0	143
SPC 1000x8	8SPC1000	8	1000	1009,6	5	5050	125	267	937		213	127	43,0	43,0	190
SPC 1250x8	8SPC1250	8	1250	1259,6	5	5050	125	267	1187		213	127	43,0	43,0	251




info@transflex.nu


KILREMSSKIVOR FÖR TAPER LOCK BUSSNING

V-BELTS PULLEYS FOR TAPER BUSH


SPC - 10



3



5



6

Material: Gjutjärn EN-GJL-200

Bilbulten Själgång EN 682 100																
Benämning		Artikelnr.	Antal spår	dp	de	Typ	För bussning	Axelhål max	Dm	Di	E	F	L	R	S	Kg.
SPC	250x10	10SPC250	10	250	259,6	3	4040	100		194		264	102	81	81	35,50
SPC	280x10	10SPC280	10	280	289,6	3	4040	100		224		264	102	81	81	45,50
SPC	300x10	10SPC300	10	300	309,6	3	4545	110		244		264	114	75	75	57,90
SPC	315x10	10SPC315	10	315	324,6	3	4545	110		259		264	114	75	75	60
SPC	335x10	10SPC3335	10	335	344,6	3	4545	110		279		264	114	75	75	70
SPC	355x10	10SPC355	10	355	364,6	3	4545	110		299		264	114	75	75	80
SPC	400x10	10SPC400	10	400	409,6	6	5050	125	267	344	70	264	127	68,5	68,5	92
SPC	450x10	10SPC450	10	450	459,6	5	5050	125	267	394		264	127	68,5	68,5	101
SPC	500x10	10SPC500	10	500	509,6	5	5050	125	267	444		264	127	68,5	68,5	114
SPC	560x10	10SPC560	10	560	569,6	5	5050	125	267	504		264	127	68,5	68,5	111
SPC	630x10	10SPC630	10	630	639,6	5	5050	125	267	574		264	127	68,5	68,5	128
SPC	710x10	10SPC710	10	710	719,6	5	5050	125	267	654		264	127	68,5	68,5	140
SPC	800x10	10SPC800	10	800	809,6	5	5050	125	267	737		264	127	68,5	68,5	177
SPC	1000x10	10SPC1000	10	1000	1009,6	5	5050	125	267	937		264	127	68,5	68,5	222
SPC	1250x10	10SPC1250	10	1250	1259,6	5	5050	125	267	1187		264	127	68,5	68,5	298



info@transflex.nu